

Online store WWW.LYNXGEAR.LV Company: SIA LATLYNX

+371 26159668 info@lynxgear.lv, +371 26159668 Reg. No. 45403038162, VAT Reg. No. Req. No.

LV45403038162,

Legal address: Baznīcas iela 8, Aizkraukle, Aizkraukles novads, LV-5101, LATVIJA

Bank Account: LV87UNLA0050021387494 AS SEB Bank, SWIFT: UNLALV2X

## ORDER CONFIRMATION

Not Rated Yet



## Sales price 22,99 €

Salesprice with discount Incl. VAT 21%: 3,99 €









## Description

The high-quality lithium-ion (Li-Ion) rechargeable battery from ANSMANN is the ideal replacement for 1.5V disposable alkaline batteries or rechargeable 1,2 V NiMH batteries. While some battery-operated devices have problems with the lower output voltage of NiMH batteries, the ANSMANN 1,5 V Li-Ion battery is fully compatible with alkaline batteries. In addition to its rechargeability, it also scores with a constant output voltage of 1.5V over 95% of the operating time thanks to its built-in electronics. If the battery still has a residual capacity of approx. 5%, the output voltage is reduced to 1.1V to signal to the user that the battery should be replaced. The constant output voltage of the ANSMANN 1.5V Li-Ion rechargeable battery ensures, for example, that a torch always shines brightly and evenly, or that a milk frother, electric toy or shaver always runs at full power. In contrast, the voltage of alkaline batteries fluctuates between 1.6V when new and 0.9V when the battery is almost exhausted. Therefore, when using alkaline batteries, the power of many devices continues to decrease. 4× AAA Li-Ion Rechargeable battery 500 mAh, 4 in 1 USB-C charging cable

• Cell size: AAA

Cell chemistry: Lithium ion

Nominal voltage: 1,5 V • Nominal capacity: 500 mAh Minimum capacity: 400 mAh

Energy: 0,74 Wh

Page 1/2



Online store WWW.LYNXGEAR.LV
Company: SIA LATLYNX
info@lynxgear.lv, +371 26159668
Reg. No. 45403038162, VAT Reg. No.
LV45403038162,
Legal address: Baznīcas iela 8,
Aizkraukle, Aizkraukles novads,
LV-5101, LATVIJA
Bank Account: LV87UNLA0050021387494
AS SEB Bank, SWIFT: UNLALV2X

## ORDER CONFIRMATION

• Storage temperature: -20 - 25 °C

• Operating temperature: -20 - 60 °C Number of cells in packaging: 4

Made in Germany.

Page 2/2