



Online store WWW.LYNXGEAR.LV
Company: SIA LATLYNX
info@lynxgear.lv, +371 26159668
Reg. No. 45403038162, VAT Reg. No.
LV45403038162,
Legal address: Baznicas iela 8,
Aizkraukle, Aizkraukles novads,
LV-5101, LATVIJA
Bank Account: LV87UNLA0050021387494
AS SEB Bank, SWIFT: UNLALV2X

ORDER CONFIRMATION

Not Rated Yet



Sales price 169,00 €

Salesprice with discount

Incl. VAT 21%: 29,33 €

1-2 months



Description

The camp cot bed is designed for use on deployment operations, training, and other military uses in field conditions.

The Camp-Cot Bed is a lightweight and space efficient bed, as previously supplied to UK forces.

- Compatible with a camp-cot bed-mounted mosquito net and a free standing mosquito net
- Compatible with the mattresses supplied (optional)
- Robust and resistant to tears, puncture and stretching, and minor repairs are possible in field
- Compatible with a roll mat
- Deployable in under 5 minutes
- Stable on moderately uneven ground
- Manufactured of proofed fabric
- One person carry
- Flame retardant
- Typically 5 year service life
- Comfortable for 8+ hours



Online store WWW.LYNXGEAR.LV
Company: SIA LATLYNX
info@lynxgear.lv, +371 26159668
Reg. No. 45403038162, VAT Reg. No.
LV45403038162,
Legal address: Baznicas iela 8,
Aizkraukle, Aizkraukles novads,
LV-5101, LATVIJA
Bank Account: LV87UNLA0050021387494
AS SEB Bank, SWIFT: UNLALV2X

ORDER CONFIRMATION

- Strong
- Stable
- Non liquid-absorbent
- Constructed from anti-corrosion treated, lightweight alloy.
- End bars have 9mm holes drilled to one side only for the mosquito-net pole insertion: 13mm from the end of the aluminium bar, 11mm from each side (measuring to the edge of the hole and not the centre-point).
- Thickness of Aluminium material approx. 1.4mm
- cover 500 D Polyester material
- Packed size: 97L x 18W x 20Hcm
- Unpacked size: 196L x 76W x 44Hcm
- Weight: 7.5 kg
- Packed in a carry-bag with zipped closure
- Designed to be stackable, when packed

NATO approved: NSN-7105-99-669-8141 Manufactured to: ISO 9001/2008
Tested to conform to: EN 581-1: 2006 EN 581-2: 2009
LOAD CAPACITY: 160 kg