

Online store WWW.LYNXGEAR.LV Company: SIA LATLYNX

info@lynxgear.lv, +371 26159668 Reg. No. 45403038162, VAT Reg. No. LV45403038162,

Legal address: Baznīcas iela 8, Aizkraukle, Aizkraukles novads, LV-5101, LATVIJA

Bank Account: LV87UNLA0050021387494 AS SEB Bank, SWIFT: UNLALV2X

ORDER CONFIRMATION

Not Rated Yet

Sales price 85,95 €

Salesprice with discount Incl. VAT 21%: 14,92 €





Description

Enjoy beach life with the new innovative TONTO BEACH TENT 3. The beach tent can be set up and taken down quick. The ridge pole and the two small poles are clipped to the tent, the Velcro sand pockets can be filled with sand for good ground fixation, so TONTO can be set-up even without pegging out all guy lines. It offers reliable UV protection and shields from wind and sun reliably.

Features

- Quarter dome construction with large opening
- PU coated fly, sealed seams
- Velco sand pockets
- Pole, pegs & guy lines included
- Light fabrics & components
- Reflective guy lines

Advantages

- Good all-round strength, easy to set up
- Fly sheet is waterproof
- Fabric shields from UVA/UVB radiation
- · Can be detached and filled with sand to anchor the beach tent
- The beach tent is ready for set-up
- Low weight & reduced pack size

Page 1/2



Online store WWW.LYNXGEAR.LV Company: SIA LATLYNX info@lynxgear.lv, +371 26159668 Reg. No. 45403038162, VAT Reg. No. LV45403038162,

Legal address: Baznīcas iela 8, Aizkraukle, Aizkraukles novads, LV-5101, LATVIJA

Bank Account: LV87UNLA0050021387494 AS SEB Bank, SWIFT: UNLALV2X

ORDER CONFIRMATION

Guy lines can be spotted in the dark better

Benefits

- Enjoy beach life, protected from wind & sun
- You stay dry no matter the rain intensity
- Inside the beach tent you are safe from UV rays*
- Easy ground fixation on sand, easy to empty
- No need to buy accessories go out & pitch it
- Carry less or bring more with you
- Let you find your camp & prevent tripping over

Flysheet

Water column Flysheet

Floor fabric

Water column Floor fabric

Poles

Pegs:

68D 190T 100% Polyester PU

3000 mm

Polyethylene with PU coating

4000 mm

Glass fibre Steel



