

Online store WWW.LYNXGEAR.LV Company: SIA LATLYNX

info@lynxgear.lv, +371 26159668 Reg. No. 45403038162, VAT Reg. No.

LV45403038162,

Legal address: Baznīcas iela 8, Aizkraukle, Aizkraukles novads, LV-5101, LATVIJA

Bank Account: LV87UNLA0050021387494 AS SEB Bank, SWIFT: UNLALV2X

<u>ORDER CONFIRMATION</u>

Not Rated Yet

Sales price 165,00 €

Salesprice with discount Incl. VAT 21%: 28,64 €







Description

19315, the new generation of German Lensolux rifle scopes with the illuminated Mil-Dot cross. Variable magnification 3-12x, lens diameter 42 mm. Resistant to gun recoil, excellent for sport shooting, perfect for strong air rifles. Smaller lens diameter allows for low mounting.

Bright, clear images, instant sharpening, multilayer lens coatings and a balanced price/performance ratio are the distinguishing features of Lensolux products. All Lensolux sights are subjected to earth-overload tests <1.5 G. The spotting scopes guarantee the shock resistance of large calibre ammunition like .375.

Reticle - Mil Dot with red illuminated crosshair and 11-stage brightness adjustment. Consists of a thinner, non-obtrusive dot cross and four beams, the mesh size always remains the same. One of the best reticles used in optical scopes, allows precise aiming in all weather conditions, even in low light.

Resistance - the high quality of the crosshairs guarantees resistance to mechanical shocks, protects against lens evaporation (argon-filled tube) and thus its water resistance.

Tubus - one-piece 1 inch diameter (25.4 mm) made of light and durable anodized aluminum. Covered with a matt non-reflective black non-reflective coating.

Page 1/2

Online Compar info@l

Online store WWW.LYNXGEAR.LV Company: SIA LATLYNX

info@lynxgear.lv, +371 26159668

Reg. No. 45403038162, VAT Reg. No. LV45403038162,

Legal address: Baznīcas iela 8, Aizkraukle, Aizkraukles novads, LV-5101, LATVIJA

Bank Account: LV87UNLA0050021387494 AS SEB Bank, SWIFT: UNLALV2X

ORDER CONFIRMATION

Mounting - Includes a sturdy, two-piece, 4-bolt low-profile 11 mm, prism rail mounting. Rear mounting allows the use of an additional screw as a stopper.

Illuminated reticle, protective eyepiece and lens caps, two-piece 11 mm rail mounting, wrench, spare CR 2032 battery and glass cleaning cloth - included.

Technical data:

- Product code: 19315
- Name: Lensolux 3-12x42E
- Magnification: 3-12x
- Lens diameter: 42 mm
- Reticle: Mil Dot
- Reticle illumination: Yes
- Exit pupil: 3.5-11.5 mm
- Field of vision at 100 m: 3.5-11.5 m
- Distance / distance from eye: 70-75 mm
- Tube diameter: 25.4 mm / 1"
- Overall length: 319.0 mm / 12.56".
- Installation: Two-piece, LR for 11 mm rail
- Weight with mounting: 570 g / 20.11 oz
- Click value per 100 yards: 1/4"
- Shock resistance: YES
- Fog resistance: YES
- Water resistance: YES
- Finish: Black Matt
- Manufacturer: Simbatec GmbH, Germany

Page 2/2