



Online store WWW.LYNXGEAR.LV
Company: SIA LATLYNX
info@lynxgear.lv, +371 26159668
Reg. No. 45403038162, VAT Reg. No.
LV45403038162,
Legal address: Baznicas iela 8,
Aizkraukle, Aizkraukles novads,
LV-5101, LATVIJA
Bank Account: LV87UNLA0050021387494
AS SEB Bank, SWIFT: UNLALV2X

ORDER CONFIRMATION

Not Rated Yet

Sales price 430,00 €

Salesprice with discount

Incl. VAT 21%: 74,63 €



1-4 Weeks



Description

Extremely robust protective case made of polypropylene for transporting electronics, equipment and other sensitive objects. The case is very impact resistant and waterproof according to IP67. Equipped with extremely sturdy hinges, smooth-running two-stage latches and an automatic pressure equalisation valve with sealing ring. The latches are high-strength injection-moulded parts that can withstand very strong impacts. The rubberised carrying handle is ergonomically shaped. The ring eyelets allow the box to be secured with an additional lock. From the 2300 size upwards, the eyelets are reinforced with stainless steel. The cubed foam insert is included and can be customised as desired. Due to its dimensions, the 2600 protective case has wheels and an additional handle. This means that the case follows you wherever you go, taking the weight off your shoulders.

- dust and waterproof according to IP67
- extremely sturdy hinges
- smooth-running, two-stage latches
- ergonomic, rubberised handles
- eyelets for securing with a lock (from 2300's stainless steel reinforced)
- automatic pressure equalisation valve with seal

Technical parameters:



Online store WWW.LYNXGEAR.LV
Company: SIA LATLYNX
info@lynxgear.lv, +371 26159668
Reg. No. 45403038162, VAT Reg. No.
LV45403038162,
Legal address: Baznicas iela 8,
Aizkraukle, Aizkraukles novads,
LV-5101, LATVIJA
Bank Account: LV87UNLA0050021387494
AS SEB Bank, SWIFT: UNLALV2X

ORDER CONFIRMATION

- Dimensions L 135,5 W 42,0 H 18,5 cm
- Inside-dimensions L 129,2 W 35,7 H 14,9 cm
- IP67
- Polypropylene
- With carrying handle
- With wheels
- Impact resistance: IK08
- Temperature stability: -25°C to +80°C
- Lid depth 48 mm
- Base depth 101 mm
- Weight 9,20 kg
- Buoyancy 67,30 kg

Brand country - Germany.