GEAR Online store WWW.LYNXGEAR.LV Company: SIA LATLYNX info@lynxgear.lv, +371 26159668 Reg. No. 45403038162, VAT Reg. No. LV45403038162, Legal address: Baznīcas iela 8, Aizkraukle, Aizkraukles novads, LV-5101, LATVIJA Bank Account: LV87UNLA0050021387494 AS SEB Bank, SWIFT: UNLALV2X

LYNX

ORDER CONFIRMATION



Not Rated Yet

Sales price 379,00 €

Salesprice with discount Incl. VAT 21%: 65,78 €

Interior: 47.1 × 25.2 × 27.7 cm Exterior: 53 × 32.3 × 32.4 cm

1-4 Weeks \star \star \star \star



Description

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

These tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware. Overview:

- Top lid opens up to 180° for on-the-field anti-roll stability when open
- Pick N Pluck $\ensuremath{^{\rm M}}$ with convoluted lid foam
- Watertight, crushproof, and dustproof
- Open cell core with solid wall design strong, light weight
- Easy open double-throw latches
- Fold down handles
- Comfortable rubber over-molded top and side handles
- Stainless steel hardware and padlock protectors
- Automatic Pressure Equalization Valve balances interior pressure, keeps water out
- O-ring seal



• Made in USA

SPECIFICATION

DIMENSIONS:

Interior (L×W×D) 18.54 x 9.92" x 10.92 (47.1 x 25.2 x 27.7 cm)
Exterior (L×W×D) 20.85 x 12.73" x 12.75 (53 x 32.3 x 32.4 cm)
Lid Depth 4.91" (12.5 cm)
Bottom Depth 6.01" (15.3 cm)
Total Depth 10.92" (27.7 cm)
Int Volume 1.16 ft³ (0.033 m³)
Padlock Hole Diameter 8 mm

MATERIALS:

Body: Polypropylene Latch: ABS O-Ring: Polymer Pins: Stainless Steel Foam: 1.3 lb Polyurethane Purge Body: ABS Purge Vent: 3 Micron Hydrophobic Non-Woven

COLORS: black, Desert tan, yellow

WEIGHT: Weight With Foam 12.48 lbs (5.7 kg) Weight Empty 8.75 lbs (4 kg) Buoyancy 82.00 lbs (37.2 kg) TEMPERATURE: Minimum Temperature -40°F (-40 °C) Maximum Temperature 210°F (99 °C) CERTIFICATIONS:

IP67

OTHER :

Military yes

Several accessories are available with seperate request: replacement foam set

Documents:

• MIL STD 810G Fungus Test

Made in USA.

All trademarks are registered and/or unregistered trademarks of Peli Products, S.L.U., its parent, subsidiaries and/or affiliates.