



Online store [WWW.LYNXGEAR.LV](http://WWW.LYNXGEAR.LV)  
Company: SIA LATLYNX  
info@lynxgear.lv, +371 26159668  
Reg. No. 45403038162, VAT Reg. No.  
LV45403038162,  
Legal address: Baznicas iela 8,  
Aizkraukle, Aizkraukles novads,  
LV-5101, LATVIJA  
Bank Account: LV87UNLA0050021387494  
AS SEB Bank, SWIFT: UNLALV2X

## ORDER CONFIRMATION

Not Rated Yet

**Sales price 805,00 €**

Salesprice with discount

Incl. VAT 21%: 139,71 €



<b>Interior Dimensions (L×W×D)</b>	71.6 × 50.2 × 44.8 cm
<b>Exterior Dimensions (L×W×D)</b>	80 × 58.1 × 48.3 cm
<b>Lid Depth</b>	8.9 cm
<b>Bottom Depth</b>	35.9 cm
<b>Total Depth</b>	44.8 cm
<b>Interior Volume</b>	0.161 m <sup>3</sup>
<b>Padlock Hole Diameter</b>	8 mm
<b>Weight (with foam)</b>	19.1 kg
<b>Weight (empty)</b>	15.5 kg
<b>Buoyancy</b>	159 kg
<b>Body Material</b>	Polypropylene
<b>Latch Material</b>	ABS
<b>Hardware</b>	Stainless steel
<b>Foam Material</b>	1.3 lb Polyurethane
<b>Purge Valve</b>	Automatic with 3-micron hydrophobic



Online store [WWW.LYNXGEAR.LV](http://WWW.LYNXGEAR.LV)  
Company: SIA LATLYNX  
info@lynxgear.lv, +371 26159668  
Reg. No. 45403038162, VAT Reg. No.  
LV45403038162,  
Legal address: Baznicas iela 8,  
Aizkraukle, Aizkraukles novads,  
LV-5101, LATVIJA  
Bank Account: LV87UNLA0050021387494  
AS SEB Bank, SWIFT: UNLALV2X

## ORDER CONFIRMATION

	vent
Temperature Range	-40 °C to +88 °C
Wheels	4 polyurethane with stainless bearings
Extendable Handle	Yes
Certifications	IP67 / DEF STAN 81-41 / MIL-STD 810G (Fungus test)

## Downloads

- [DEF STAN 81-41 Certification \(PDF\)](#)
- [1660 IP67 Certification \(PDF\)](#)
- [MIL-STD 810G Fungus Resistance Test \(PDF\)](#)

## Why Choose the PELI 1660EU Protector Case?

- **Unmatched protection:** Watertight, dustproof, crushproof - engineered for the toughest conditions
- **Military-grade certification:** IP67 and DEF STAN 81-41 compliant for professional and defense applications
- **Versatile mobility:** Four durable wheels and a retractable handle for effortless transport
- **Customizable interior:** Includes Pick N Pluck™ foam for personalized fit and equipment safety
- **Temperature resistant:** Performs from -40°C to +88°C

## Glossary

- **IP67:** International protection rating ensuring dust-tightness and submersion resistance up to 1 meter for 30 minutes.
- **DEF STAN 81-41:** British military standard for robust, shock-resistant protective cases.
- **Pick N Pluck™ Foam:** Pre-scored foam that allows easy customization to fit specific equipment shapes.
- **Automatic Pressure Valve:** Equalizes internal air pressure to prevent vacuum lock during altitude or temperature changes.

## Manufacturer

**Peli Products, S.L.U.** (EU Representative of Peli, USA)

c/ Provença, 388, Planta 7

08025 Barcelona, Spain

Phone: +34 934 674 999

Email: This email address is being protected from spambots. You need JavaScript enabled to view it.



Online store [WWW.LYNXGEAR.LV](http://WWW.LYNXGEAR.LV)  
Company: SIA LATLYNX  
info@lynxgear.lv, +371 26159668  
Reg. No. 45403038162, VAT Reg. No.  
LV45403038162,  
Legal address: Baznicas iela 8,  
Aizkraukle, Aizkraukles novads,  
LV-5101, LATVIJA  
Bank Account: LV87UNLA0050021387494  
AS SEB Bank, SWIFT: UNLALV2X

---

## **ORDER CONFIRMATION**

---

```
document.getElementById('cloak2e5be10a1214447311880e4ec7d277a1').innerHTML
= ''; var prefix = 'ma' + 'il' + 'to'; var path = 'hr' + 'ef' + '='; var
addy2e5be10a1214447311880e4ec7d277a1 = 'info' + '@';
addy2e5be10a1214447311880e4ec7d277a1 = addy2e5be10a1214447311880e4ec7d277a1
+ 'peli' + '.' + 'com'; var addy_text2e5be10a1214447311880e4ec7d277a1 =
'info' + '@' + 'peli' + '.' + 'com';document.getElementById('cloak2e5be10a1
214447311880e4ec7d277a1').innerHTML +=
'+addy_text2e5be10a1214447311880e4ec7d277a1+';
Website: www.peli.com
```

© Peli Products, S.L.U. / Peli USA. Specifications may change without notice for product improvement.