

Online store WWW.LYNXGEAR.LV Company: SIA LATLYNX

+371 26159668 info@lynxgear.lv, +371 26159668 Reg. No. 45403038162, VAT Reg. No. Req. No.

LV45403038162,

Legal address: Baznīcas iela 8, Aizkraukle, Aizkraukles novads, LV-5101, LATVIJA

Bank Account: LV87UNLA0050021387494 AS SEB Bank, SWIFT: UNLALV2X

ORDER CONFIRMATION

Not Rated Yet

Sales price 560,00 €



Salesprice with discount Incl. VAT 21%: 97,19 €

> Interior: $128.3 \times 34.3 \times 13.3$ cm Exterior: $134.6 \times 40.6 \times$

15.5 cm

1-4 Weeks ★ ★ ☆ ☆ ☆



Description

Sensitive equipment needs protection, and since 1976 the answer has been the $Peli^{m}$ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, overmolded rubber handles and stainless steel hardware. Overview:

- 3-piece foam set
- Strong polyurethane wheels with stainless steel bearings
- Watertight, crushproof, and dustproof
- Open cell core with solid wall design strong, light weight
- Easy open double-throw latches
- Fold down handles
- Stainless steel hardware and padlock protectors
- Automatic Pressure Equalization Valve balances interior pressure, keeps water out
- O-ring seal

SPECIFICATION

DIMENSIONS:

Interior (L×W×D) 50.50 x 13.50" x 5.25 (128.3 x 34.3 x 13.3 cm) Exterior (L×W×D) 53.00 x 16.00" x 6.12 (134.6 x 40.6 x 15.5 cm)

Page 1/2

Online store WWW.LYNXGEAR.LV Company: SIA LATLYNX

info@lynxgear.lv, +371 26159668 Reg. No. 45403038162, VAT Reg. No. LV45403038162,

Legal address: Baznīcas iela 8, Aizkraukle, Aizkraukles novads, LV-5101, LATVIJA

Bank Account: LV87UNLA0050021387494 AS SEB Bank, SWIFT: UNLALV2X

CONFTRMATION
Lid Depth 1.75" (4.4 cm) Bottom Depth 3.50" (8.9 cm) Total Depth 5.25" (13.3 cm) Int Volume 2.07 ft 3 (0.059 m 3)

Padlock Hole Diameter 5/16" (12.7 cm)

MATERIALS:

Body: Polypropylene

Latch: ABS O-Ring: Polymer

Pins: Stainless Steel Foam: 1.3 lb Polyurethane

Purge Body: ABS

Purge Vent: 3 Micron Hydrophobic Non-Woven

COLORS: black, OD green, Desert tan

WEIGHT:

Weight With Foam 25.57 lbs (11.6 kg) Weight Empty 23.59 lbs (10.7 kg) Buoyancy 187.39 lbs (85 kg)

Master Pack Weight 25.65 lbs (11.6 kg)

TEMPERATURE:

Minimum Temperature -40°F (-40 °C) Maximum Temperature 210°F (98.9 °C)

CERTIFICATIONS:

IP67

Def Stan 81-41 STANAG 4280

OTHER:

Wheels 2

Master Pack 1 Nameplate yes

Military yes

Several accessories are available with seperate request: replacement foam set, replacement O-ring

Documents:

- DEF STAN 81 41
- 1750 IP67
- MIL STD 810G Fungus Test

Made in USA.

Page 2/2