



Online store WWW.LYNXGEAR.LV
Company: SIA LATLYNX
info@lynxgear.lv, +371 26159668
Reg. No. 45403038162, VAT Reg. No.
LV45403038162,
Legal address: Baznicas iela 8,
Aizkraukle, Aizkraukles novads,
LV-5101, LATVIJA
Bank Account: LV87UNLA0050021387494
AS SEB Bank, SWIFT: UNLALV2X

ORDER CONFIRMATION

Not Rated Yet

Sales price 724,95 €

Salesprice with discount

Incl. VAT 21%: 125,82 €



Description

Perfect for 24-hour shooting and hunting activities, the Sightmark Wraith 4K 4-32x40 day/night digital riflescope's 4K (3840x2160) CMOS sensor provides full-color HD imaging for daytime shooting and transitions to digital night vision with a 274-meter/300-yard detection range with the push of a button.

The Wraith 4K's high-resolution 1280x720 display delivers crystal-clear imaging while the 4-32x digital magnification gives users the versatility to adjust for close- to mid-range targets. The Wraith 4K is designed for all hunting applications including small game, boar, predator and even deer.

The included LED IR illuminator emits an 850nm beam to help maximize positive target identification, while 10 reticle styles with 9 colors, give users full control over customizing the Wraith's field of view. Built to handle tough environments, the Wraith 4K is recoil-rated up to .308 Winchester and features solid aluminum construction with IP55 water-resistant protection and an operating temperature range from - 6 to + 50C (20 to 122F).



Online store WWW.LYNXGEAR.LV
Company: SIA LATLYNX
info@lynxgear.lv, +371 26159668
Reg. No. 45403038162, VAT Reg. No.
LV45403038162,
Legal address: Baznicas iela 8,
Aizkraukle, Aizkraukles novads,
LV-5101, LATVIJA
Bank Account: LV87UNLA0050021387494
AS SEB Bank, SWIFT: UNLALV2X

ORDER CONFIRMATION

Included in Package

- 850nm IR Illuminator
- Objective lens cover
- Fixed Picatinny mount
- Eye cup
- Quick Start Guide

Battery Used

- Type: 4xAA
- Quantity: 1

Product Downloads

- [User Manual – English](#)
- [Quick Start Guide](#)
- [How to Update Wraith 4K Firmware](#)

Features

- 4K, CMOS sensor
- Variable 4-32x magnification
- Built-in video recording with audio in 4K
- Night vision mode
- Daytime color mode
- 274 meters / 300 yards NV detection range
- Lens cap design with an integrated daytime lens filter
- USB port

Specification:

Electronic components

Type of sensor	CMOS sensor
Sensor resolution, pixels	4K (3840x2160)
Display type	FLCOS
Display Resolution, pix.	1280x720
Built-In Video Recorder Availability	Yes
Maximum memory card supported, Gb	256
Format of video clip	AVI
Resolution of video clip	1080/4K
Format of photo files	JPEG
Resolution of photo files	4k
Memory capacity	Approximately 1.75 hours video with 64gb SD card on 4k@30 quality level.

Optical characteristics



Online store WWW.LYNXGEAR.LV
Company: SIA LATLYNX
info@lynxgear.lv, +371 26159668
Reg. No. 45403038162, VAT Reg. No.
LV45403038162,
Legal address: Baznicas iela 8,
Aizkraukle, Aizkraukles novads,
LV-5101, LATVIJA
Bank Account: LV87UNLA0050021387494
AS SEB Bank, SWIFT: UNLALV2X

ORDER CONFIRMATION

Magnification	4-32
Lens diameter, mm	40
Digital zoom	1-8x
Field of View, °, horizontal	4
Field of View, m@100m>	7
Field of View, ft@100yd>	21
Minimum focusing distance, ft/m	12 / 3.6
Eye Relief, in/mm	2.4 / 60
Diopter adjustment, dptr.	-6 to +3

IR-illuminator

Emitter	LED
IR Wavelength, nm	850nm
Equivalent IR Power, mW	~1060 on high, ~540 on medium, ~400 on low
Battery Life	2 hours on high
Battery type	2x CR123A

Range of Detection

Night Vision detection range, yd/m	300/274
------------------------------------	---------

Power Supply

Power Supply, v	6
Battery type	4x AA
Battery life	3.6Hrs Video Mode/ 4.4Hrs Preview Mode
External Power Supply	5V via microUSB

Reticle

Windage & Elevation click value	1 pixel/ ~X0.4MOA
Adjustment range, elevation	~ 92 MOA
Adjustment range, windage	~ 215 MOA
Number of reticle options	10
Colors	Black, white, red, blue, green, cyan, orange, yellow, magenta

Physical & operational characteristics

Body Material	Aluminum
Accessory rail mount	Picatinny
Operating Temp, °F / C°	32 to 140 / 0 to 60
Waterproof rating	IPX6 - water resistant
Nitrogen Purged, yes/no	no
Shockproof, yes/no	yes, 3ft
Maximum recoil, caliber	.308
Tube diameter	n/a
Length, in/mm	10.5 / 266
Width, in/mm	1.875 / 63
Height, in/mm	3 / 75
Weight (with batteries), oz/g	37.6 / 1066
Brand country - U.S.	