



Online store [WWW.LYNXGEAR.LV](http://WWW.LYNXGEAR.LV)  
Company: SIA LATLYNX  
info@lynxgear.lv, +371 26159668  
Reg. No. 45403038162, VAT Reg. No.  
LV45403038162,  
Legal address: Baznicas iela 8,  
Aizkraukle, Aizkraukles novads,  
LV-5101, LATVIJA  
Bank Account: LV87UNLA0050021387494  
AS SEB Bank, SWIFT: UNLALV2X

---

## ORDER CONFIRMATION

---

Not Rated Yet



**Sales price 84,99 €**

Salesprice with discount

Incl. VAT 21%: 14,75 €

**7 Days**  
★★★★★



### Description

The sighting compass for experienced navigators - used by NATO Forces around the world. Mainly used by the infantry as a soldier's or officer's compass. Additional features include measuring scales for positioning (GPS), graduation in mils and degrees (360/6400), integrated adjuster for magnetic declination, magnifying lens and rubber feet for precision map work. The compass has a luminous graduation ring and markings for compass reading in the dark. Once activated by daylight/flashlight it will give light up to 4 hours of light. The included scale lanyard and slope card makes it easier to quickly make a distance judgement of your route or to plan your route in advance.

- Compass capsule / needle Liquid filled capsule
- Sapphire jewel bearing
- High quality steel needle
- Hardened steel pivot
- Sighting System Mirror



Online store [WWW.LYNXGEAR.LV](http://WWW.LYNXGEAR.LV)  
Company: SIA LATLYNX  
info@lynxgear.lv, +371 26159668  
Reg. No. 45403038162, VAT Reg. No.  
LV45403038162,  
Legal address: Baznicas iela 8,  
Aizkraukle, Aizkraukles novads,  
LV-5101, LATVIJA  
Bank Account: LV87UNLA0050021387494  
AS SEB Bank, SWIFT: UNLALV2X

---

## ORDER CONFIRMATION

---

- Magnifying lens
  - Declination adjustment
  - Clinometer
  - Luminous markings
  - Luminaous graduation ring
  - Illumination / active time, after activation in light 4 hours
  - Silicon friction feet
  - Other: Tactile grip ring, Patented red/black N/S lines in capsule, GPS scales, Complete baseplate cover
- 
- Graduation: 360/6400
  - Resolution mils / degrees: 50 / 2
  - Measuring scales: Base plate - mm, inch
  - UTM position plotting scales (Romer scales): 1:25k, 1:50k
  - Settling time from 90 degree angle within +/- 3 deg: 2.7 sec
  - Settling time from 90 degree angle to complete rest: 5 sec
  - Accuracy: +/- 17.8 mils / 1 degree
  - Water resistance: Waterproof
  - Altitude use: 5000. -15C
  - Impact resistance: 30g in XYZ directions and free fall from 1,5 m height into gravel
  - Temperature operating range: -30 to +60 C
  - Material Acrylic/PC/ABS/TPU/Acetal
  - Size: 108x64x20mm
  - Weight: 86g

Brand country - Sweden.